

Unique Features

- Solvent Based
- Fast Drying
- Good Opacity
- Excellent Adhesion, Flexibility &
- Stretchability
- Good abrasion Resistance
- Gives Higher Productivity & Profitability
- Suitable for Machine & Manual Printing
- Good Screen Stability
- Good Durability with Water

Color Range

- Fluorescent Colors
- SYNORUB Standard Colors
- Custom Made Colors can be supplied against wet ink, print or PANTONE ® reference

Substrates

EVA & Rubber

Printability

Excellent Printability with Good Coverage

Thinning & Cleaning

SYNORUB inks are ready to use. If you need to thin the ink, use Superscreen Thinner (less than 5%).

Pre-Production Test

Always test for Adhesion (by Cross cut tape test [ASTM 3359]) & other properties before each production run because there can often be significant difference between substrate from different manufactures and even between different batches.

Specially, Cleanliness of the slipper is required before printing.

For Excellent Abrasion Resistance

It is better to manufacture EVA sheets with pin holes (or minute cavity) on the surface during the moulding process. When you apply the ink, it will fill to the pin holes & excellent abrasion property is developed.

Drying

Normally up to one minute for air-drying.

Storage

Stir well before use. Keep Ink away from direct sunlight. Keep lids tightly closed when not in use. Any unused ink should not be returned to the container, must store separately.

Safety & Handling

Most of our inks are manufactured free of heavy metals. SYNORUB Inks are Solvent based. When you handle inks; wear mask, safety goggles & chemical resistant gloves. Use well ventilated working place.

Important

The information and recommendations contained in this Product Information Sheets are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our product.